

# ZCKD23

limit switch head ZCKD - steel roller lever  
plunger with protective boot



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Plunger head
Product compatibility	XCKM XCKL
Associated body	ZCKMD37H7 ZCKMD31H29 ZCKM6H29 ZCKM1H29 ZCKMD37H29 ZCKM9 ZCKM8H7 ZCKL5H7 ZCKL6 ZCKM6 ZCKLD39 ZCKL1 ZCKM1H7 ZCKM5 ZCKM8H29 ZCKLD37H7 ZCKL1H7 ZCKLD39H7 ZCKM6H7 ZCKM1 ZCKMD35H29 ZCKL7H7 ZCKMD39 ZCKM8 ZCKMD31H7 ZCKMD39H29 ZCKLD35 ZCKMD37 ZCKM7 ZCKLD37 ZCKMD39H7 ZCKM9H29 ZCKMD31 ZCKL5 ZCKL6H7 ZCKLD31H7 ZCKMD35 ZCKM7H29 ZCKM5H29 ZCKLD35H7 ZCKMD35H7 ZCKL8 ZCKM5H7 ZCKL7 ZCKLD31 ZCKL8H7 ZCKM7H7
Movement of operating head	Rotary Linear
Type of operator	Roller lever plunger spring return metal
Type of approach	Lateral approach, 1 direction

## Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

## Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

### Packing Units

Package 1 Weight	0.096 Kg
Package 1 Height	0.330 Dm
Package 1 width	0.630 Dm
Package 1 Length	0.750 Dm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**