

Rittal – The System.

Faster – better – everywhere.



SK 3383.600

TopTherm Blue e roof-mounted cooling unit

State: 28/02/2022 (Source: rittal.com/com-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3383.600 - TopTherm Blue e roof-mounted cooling unit

Total cooling output 0.50 - 4.00 kW

Energy-efficient Blue e roof-mounted cooling units in output categories from 500 W to 4,000 W, with integral e-Comfort controller, RiNano coating on the condenser and electrical condensate evaporation as standard.

Features

Product description	Energy-efficient Blue e roof-mounted cooling units with integral e-Comfort controller, RiNano coating on the condenser and electric condensate evaporation as standard.
Benefits	May be linked to the IoT interface via Blue e IoT adaptor for cooling units from 500 W cooling output with e-Comfort controller
Material	Stainless steel 1.4301 (AISI 304)
Colour	RAL 9007
Supply includes	Nano-coated condenser Integral electric condensate evaporation Fully wired ready for connection (plug-in terminal strip) Drilling template Assembly parts
Total cooling output to DIN EN 14511	Cooling output L35 L35/50 Hz: 1 kW Cooling output L35 L35/60 Hz: 1.09 kW Cooling output L35 L50/50 Hz: 0.71 kW Cooling output L35 L50/60 Hz: 0.81 kW
Rated operating voltage	230 V, 1~, 50 Hz/60 Hz
Rated current max.	At 50 Hz: 2.9 A At 60 Hz: 3.9 A
Start-up current max.	At 50 Hz: 8.8 A At 60 Hz: 10.1 A
Air throughput (unimpeded air flow)	External circuit: 1,600 m ³ /h Internal circuit: 491 m ³ /h
Energy efficiency ratio (EER) 50/60 Hz L35 L35	Refrigeration factor L35 L35 (EER) 50 Hz: 2.58 Refrigeration factor L35 L35 (EER) 60 Hz: 2.28

Features

Design	roof-mounted
Dimensions	Width: 597 mm Height: 417 mm Depth: 475 mm
Note on Model No.	Extended delivery times.
Protection category to IEC 60 529	External circuit IP 34 Internal circuit IP 54
Refrigerant/cooling medium	Refrigerant: R134a Quantity: 0.65 kg Global Warming Potential (GWP): 1,430 CO2 equivalent (CO2e): 0.93 t
Type of electrical connection	Plug-in terminal strip
Duty cycle	100 %
Temperature control	e-Comfort controller (factory setting +35 °C)
Operating temperature range	10 °C...55 °C
Storage temperature range	-40 °C...70 °C
Setting range	20 °C...55 °C
Power consumption Pel	Power consumption L35 L35/50 Hz: 0.38 kW Power consumption L35 L35/60 Hz: 0.47 kW Power consumption L35 L50/50 Hz: 0.43 kW Power consumption L35 L50/60 Hz: 0.55 kW
Permissible operating pressure (p. max.)	28 bar
Pre-fuse	Miniature circuit-breaker/fuse: 10 A
Note	The roof-mounted cooling unit 3273.500 is also suitable for office applications, thanks to its low noise level.
Weight/pack	40 kg
Packs of	1 Stück
ETIM 7.0	EC000855
ECLASS 8.0	27180704

Approvals

Approvals

Approvals

CSA

UL + C-UL - FTTA

UR + C-UR

Certificates

EAC

Explanations

Declaration of conformity

Declaration of conformity - F-gas regulation

Tender text

3383600

Roof-mounted cooling unit TopTherm Blue e

Energy-efficient Blue e roof-mounted cooling units with integral e-Comfort controller, RiNano coating on the condenser and electric condensate evaporation as standard.

Total cooling output L35 L35 50/60 Hz: 1,0 / 1,09 kW

Total cooling output L35 L50 50/60 Hz: 0,71 / 0,81 kW

Power consumption L35 L35 50/60 Hz: 0,38 / 0,47 kW

Power consumption L35 L50 50/60 Hz: 0,43 / 0,55 kW

Rated power input 50/60 Hz: 2,9 / 3,9 A

Rated operating voltage: 230 V, 1~, 50/60 Hz

Temperature control: e+ controller (factory setting +35 °C)

Dimensions [WxHxD]: 597x417x475 mm

Material: Stainless steel 1.4301 (AISI|304)

Colour:

Refrigeration factor (EER) 50/60 Hz: 2,58 / 2,28

Refrigerant / Quantity:

Operating temperature range: 10 °C bis 55 °C

Setting range: 20 °C bis 55 °C

Protection category IP to IEC 60 529: Internal circuit IP 54, external circuit IP 34

Weight: 40 kg