

PRODUCT CARD



PRODUCT CODE: OR-AE-13600 EAN CODE: 5908254802089

MINI cable connector, straight, 3x1.5mm², 450V/16A

This MINI cable connector is small in size and simple in shape. High ingress protection level IP68 guarantees resistance against difficult weather conditions and an additional sealing with an O-ring secures the product against chemical and mechanical damage. The material used for connector's production is resistant to UV rays and is suitable for outdoor use. This robust and firm construction as well as our innovative sealing solution make the product suitable for underground installation. Its contacts are made of brass with additional nickel layer to secure them against oxidation. Cable gland is equipped with a thick gasket to tightly seal all cables inside.



Current: 16A

UV radiation resistance:

(ΰr)
(6)

Degree of protection (IP): 68

Case flammability standard UL94: V1



Number of wires: 3

Wire cross-section: 1,5mm²

ORNO-LOGISTIC Sp. z o. o.

ul. Rolników 437 44-141 Gliwice tel. 32 43 43 110 www.orno.pl



General information

Connector type:	screw
Cable gauge:	4-8 mm mm
Current:	16 A
Contacts material:	nickel-plated brass
Power supply:	450V
Degree of protection (IP):	68
Flame-resistant casing:	yes
Number of wires:	3
Dimensions - width:	20 mm
UV radiation resistance:	yes
Case flammability standard UL94:	V1
Dimensions - length (mm):	76 mm
Type of connection:	screw clamp
Underground installation:	yes
Wire cross-section:	1,5 mm ²
Case material:	PA6

ul. Rolników 437 44-141 Gliwice