

TECHNICAL INFORMATIONS

GU10 38° SPOTLIGHTS

6W 4000K

Linha GU10 com vários ângulos de abertura e potências para diferentes espaços.

GU10 line with several wattages and beam angles for different spaces.

Línea microicas con diferentes potencias y haz de luz para espacios variados.


ILAR-00551




REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00551	Diameter	50mm	Total Luminous Flux	480lm
Lamp type	GU10	Length	55mm	Luminous Efficacy	80lm/W
Lamp Base	GU10	Weight	30g	Beam Angle	38°
Nominal Lifetime (EOL end of life)	25000h			Colour Temperature	4000K
Switching Cycle (times)	15000X			Colour Rendering Index	80
Dimmable	No			Colour Consistency	<= 6
Mercury Free	Yes				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	6W	Energy Label	A+	ROHS	YES
Equivalent Wattage	39W	Energy Consumption KWH/1000H	6kWh	CE	YES
Lamp Current	45mA			LM70	NO
Nominal Voltage	220-240V			LM80	YES
Operating Frequency	50/60Hz			LM79	-
Power Factor	0.5			TM21	-
Starting Time	0.5s			ENEC	-
Warm-up Time (60%)	0.5s				
Operating Temperature	-30°C to + 40°C				

SIZE



BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

