

Product data sheet

Specifications



Acti9 analogue outdoor light sensor cell

CCT15263

Main

Range of product	Acti 9
Product or component type	Wall mounted cell
Function available	Horizontally orientable

Complementary

Range compatibility	Acti9 Acti 9 IC IC100 twilight switch Acti9 Acti 9 IC IC2000 twilight switch Acti9 Acti 9 IC IC2000P+ programmable twilight switch with time switch function
Cable length	50 m
Light intensity adjustment	2...2000 lux
Mounting location	Outdoor
Height	95 mm
Width	48 mm
Depth	45 mm
Net weight	40.5 g
Market segment	Residential Small commercial
Compatibility code	Wall mounted cell

Environment

Ambient air temperature for operation	-40...70 °C
Ambient air temp for storage/ transportation	-40...70 °C
Relative humidity	100 %
IP degree of protection	IP55

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	54 g
Package 1 Height	0.01 cm

Package 1 width	17 cm
Package 1 Length	12 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	606 g
Package 2 Height	12 cm
Package 2 width	10 cm
Package 2 Length	20 cm
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Weight	4.135 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins