



Earth-leakage VigiPacT add-on protection module, ComPacT NSX 400/630, 200VAC to 440VAC, 30mA to 30A, 4 poles

LV432465

EAN Code: 3606481298669

Main

Walli	
Range of product	ComPacT NSX400630 new generation ComPact NSX400630
Device short name	VigiPacT
Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	ComPacT new generation (ComPacT NSX400 new generation) circuit breaker ComPacT new generation (ComPacT NSX630 new generation) circuit breaker ComPact (ComPact NSX400) circuit breaker ComPact (ComPact NSX630) circuit breaker
Poles description	4P
[In] rated current	400 A 630 A
Earth-leakage protection class	Class A Class AC
Residual earth-leakage sensitity adjustment type	Adjustable
Earth-leakage sensitivity	0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 3 A for class A 10 A for class AC
Residual earth-leakage time delay adjustment type	Adjustable
[Δt] residual earth-leakage time delay adjustment	0 ms 60 ms 150 ms 300 ms 500 ms 800 ms 1.2 s

Complementary

•	
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	200440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	800 ms

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Overvoltage category	IV
Environment	
Electrical shock protection class	Class II
Standards	IEC 60947-2
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.000 cm
Package 1 Width	17.200 cm
Package 1 Length	19.700 cm
Package 1 Weight	3.320 kg
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	20.800 kg
Unit Type of Package 3	P12
Number of Units in Package 3	24
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	95.200 kg
Offer Suctainability	
Offer Sustainability Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Contractual warranty	
Warranty	18 months