

# Product datasheet

Specifications



Floor standing encl. polyester  
vers.PLA compl.sealed  
1250x750x420 IP65 glazed

NSYPLA1274TG

**Price\* : 21,199.29 ZAR**

## Main

|                           |  |
|---------------------------|--|
| Range                     | Thalassa   |
| Product name              | Thalassa PLA   |
| Enclosure type            | Multi-purpose  |
| Product or component type | Suitable enclosure   |
| Version                   | PLA  |
| Nominal height            | 1250 mm  |
| Nominal width             | 750 mm   |
| Nominal depth             | 420 mm   |
| Enclosure mounting        | Floor-standing   |
| Device composition        | 1 top part<br>1 bottom part<br>2 side part<br>1 rear panel<br>1 door |

## Complementary

|                             |  |
|-----------------------------|--|
| Body type                   | Sealed top and bottom part assembled with side parts                   |
| Door type                   | Transparent front  |
| Number of doors             | 1 door(s)  |
| Door opening side           | Reversible (120 °)   |
| Lock type                   | 4 points lock, 5 mm double-bar   |
| Accessibility for operation | Front<br>Rear  |
| Removable parts             | Door by hinges<br>Rear panel by fixing element                         |
| Material                    | Polyester reinforced with fibreglass                                   |
| Colour                      | Grey (RAL 7035)  |
| Standards                   | IEC 62208<br>UL 508 A  |
| NEMA degree of protection   | NEMA 3X<br>NEMA 3<br>NEMA 3R<br>NEMA 12<br>NEMA 1<br>NEMA 5<br>NEMA 3S |

\* Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

NEMA 13  
NEMA 2

---

|                               |  |
|-------------------------------|--|
| <b>Product certifications</b> | DNV Marine<br>Veritas<br>UL/cUL listed |
|-------------------------------|--|

---

|                                    |          |
|------------------------------------|----------|
| <b>Electrical insulation class</b> | Class II |
|------------------------------------|----------|

---

## Environment

---

|                                |  |
|--------------------------------|--|
| <b>IP degree of protection</b> | IP65 conforming to IEC 60529 (completely sealed) |
|--------------------------------|--|

---

|                                |  |
|--------------------------------|--|
| <b>IK degree of protection</b> | IK08 conforming to IEC 62262 (glazed door) |
|--------------------------------|--|

---

|                        |                                |
|------------------------|--------------------------------|
| <b>Fire resistance</b> | 960 °C conforming to IEC 62208 |
|------------------------|--------------------------------|

---

|  |             |
|--|-------------|
| <b>Ambient air temperature for storage</b> | -35...90 °C |
|--|-------------|

---

## Packing Units

---

|                               |     |
|-------------------------------|-----|
| <b>Unit Type of Package 1</b> | PCE |
|-------------------------------|-----|

---

|                                     |   |
|-------------------------------------|---|
| <b>Number of Units in Package 1</b> | 1 |
|-------------------------------------|---|

---

|                         |           |
|-------------------------|-----------|
| <b>Package 1 Weight</b> | 43.438 kg |
|-------------------------|-----------|

---

|                         |        |
|-------------------------|--------|
| <b>Package 1 Height</b> | 126 cm |
|-------------------------|--------|

---

|                        |       |
|------------------------|-------|
| <b>Package 1 width</b> | 78 cm |
|------------------------|-------|

---

|                         |       |
|-------------------------|-------|
| <b>Package 1 Length</b> | 45 cm |
|-------------------------|-------|

---

## Offer Sustainability

---

|                                 |                       |
|---------------------------------|-----------------------|
| <b>Sustainable offer status</b> | Green Premium product |
|---------------------------------|-----------------------|

---

|                         |                                   |
|-------------------------|-----------------------------------|
| <b>REACH Regulation</b> | <a href="#">REACH Declaration</a> |
|-------------------------|-----------------------------------|

---

|                          |   |
|--------------------------|---|
| <b>EU RoHS Directive</b> | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
|--------------------------|---|

---

|                     |     |
|---------------------|-----|
| <b>Mercury free</b> | Yes |
|---------------------|-----|

---

|                                   |                     |
|-----------------------------------|---------------------|
| <b>RoHS exemption information</b> | <a href="#">Yes</a> |
|-----------------------------------|---------------------|

---

|                              |   |
|------------------------------|---|
| <b>China RoHS Regulation</b> | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
|------------------------------|---|

---

|                                 |   |
|---------------------------------|---|
| <b>Environmental Disclosure</b> | <a href="#">Product Environmental Profile</a> |
|---------------------------------|---|

---