Product data sheet Characteristics

ZB4BP5

Push button head, metal, projecting, yellow, Ø22, spring return, booted, unmarked





Main

Range of product	Harmony XB4
Product or component type	Head for non-illuminated push-button
Device short name	ZB4
Product compatibility	Not compatible with legend holder
Bezel material	Chromium plated metal
Mounting diameter	22 Mm
Sale per indivisible quantity	1
Head type	Standard
Shape of signaling unit head	Round
Type of operator	Spring return
Operator profile	Yellow projecting, unmarked
Operator additional information	Clear boot

Complementary

Device presentation	Basic element
	C15 for <1 contacts using single blocks in front mounting
	C2 for <9 contacts using single and double blocks in front mounting C11 for <3 contacts using single blocks in front mounting
Electrical composition code	C1 for <9 contacts using single blocks in front mounting
Mechanical durability	10000000 Cycles
CAD overall depth	35 Mm
CAD overall height	30 Mm
CAD overall width	30 Mm

Environment

Protective treatment	TH	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-4070 °C	
Overvoltage category	Class I conforming to IEC 60536	
IP degree of protection	IP66 conforming to IEC 60529 IP67	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK06 conforming to IEC 50102	

Standards	EN/IEC 60947-5-5 CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60947-1 UL 508
	EN/IEC 60947-5-4 JIS C8201-5-1 JIS C8201-1
Product certifications	GL RINA CSA BV UL listed DNV LROS (Lloyds register of shipping)
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming- to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming- to IEC 60068-2-27

Packing Units

r doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	32 G
Package 1 Height	3.4 Cm
Package 1 width	4.5 Cm
Package 1 Length	5.4 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	160 G
Package 2 Height	3.4 Cm
Package 2 width	4.5 Cm
Package 2 Length	26.5 Cm
Unit Type of Package 3	S03
Number of Units in Package 3	300
Package 3 Weight	10.108 Kg
Package 3 Height	30 Cm
Package 3 width	30 Cm
Package 3 Length	40 Cm

Offer Sustainability

Onor Odolamability	
Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information

Contractual warranty

Warranty 18 months

Product Life Status :	Commercialised	
-----------------------	----------------	--

