

CAT. N° 4 076 73



## MCB - DX<sup>3</sup> 6000 - 10 KA - 1P - 230/400 V~ - 32 A - C CURVE

Pack (number of units)	10
Volume (dm <sup>3</sup> )	1,681
Weight (g)	1 428,00

### Product characteristics

#### Single pole 230/400 V~

- C curve
- Nominal rating I<sub>n</sub> : 32 A
- Number of modules : 1

### General characteristics

#### MCBs DX<sup>3</sup> 6000 - 10 kA - thermal magnetic circuit breakers from 1 A to 63 A - B and C curves

- Conform to IEC 60898-1
- Compatible with both, prong-type and fork type supply busbars
- Breaking capacity
  - 6000 - IEC 60898-1 - 400 V~
  - 10 kA - IEC 60947-2 - 400 V~
- Can be equipped with DX<sup>3</sup> signalling and remote tripping auxiliaries, motorised controls and add-on modules

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.064\)](#)
- [Dimensions of din-rail equipment](#)
- [Performance of MCBs and auxiliaries](#)

#### Agreements & certificates of conformity

- [VDE-40047508](#)
- [QC / CB-IT-10651](#)
- [QC / CB-IT-10651/M1](#)
- [QC / CB-IT-18023](#)
- [VDE-40034165](#)
- [AENOR-030/002456](#)

#### Installation & technical data

- [F01591EN-03](#)

#### Environmental product profile

- [Environnemental product sheet n°8 E0112A-FR](#)
- [LGRP-00828-V01](#)